

INTERGRAL TANDEM 3PT LIFT TYPE DISC HARROWS

D-18-1618 / D-18-1620 / D-18-1622 / D-18-1820 / D-18-2020 /
D-20-2020 / D-20-2022 / D-20-2220 / D-20-2222 / D-21-2420 / D-21-2422



These disc Harrows are designed with durable and rigid 3" (3 1/2" on model D-21) tubular frames holding gangs firmly in place. Wide range of cutting angles easily adjusted for maximum protection. Hitch places low for good rear gang penetration and handling. Cutout disc blades mounted on front and rear. Axle bearings are sealed for long life protection.

MODEL SPECIFICATIONS

	CUT WIDTH	FRONT DISC	REAR DISC	SPACING		BLADE DIAMETER	APPROX. WEIGHT	HITCH	*SUGGESTED MINIMUM TRACTOR HP
				FRONT	REAR				
D-18-1618	5-1/2'	8	8	9"	9"	18"	773lbs	Cat. 1	25HP - 30HP
D-18-1620	5-1/2'	8	8	9"	9"	0"	840lbs	Cat. 1	25HP - 30HP
D-18-1622	5-1/2'	8	8	9"	9"	22"	920lbs	Cat. 1	25HP - 30HP
D-18-1820	6-1/2'	10	10	9"	7-1/2"	20"	870lbs	Cat. 1	25HP - 30HP
D-18-2020	6-1/2'	10	10	7-1/2"	7-1/2"	20"	900lbs	Cat. 1	25HP - 30HP
D-20-2020	7-1/2'	10	10	9"	9"	20"	990lbs	Cat. 1&2	30HP - 40HP
D-20-2022	7-1/2'	10	10	9"	9"	22"	1,090lbs	Cat. 1&2	30HP - 40HP
D-20-2220	8'	10	12	9"	7-1/2"	20"	1,020lbs	Cat. 1&2	30HP - 40HP
D-20-2222	8'	10	12	9"	7-1/2"	22"	1,130lbs	Cat. 1&2	40HP - 45HP
D-21-2422	9'	12	12	9"	9"	20"	1,500lbs	Cat. 2	45HP - 55HP
D-21-2422	9'	12	12	9"	9"	22"	1,600lbs	Cat. 2	45HP - 55HP

*SUGGESTED MINIMUM HP MAY VARY DEPENDING UPON COMPOSITION OF SOIL, GANG ANGLE, AND CONDITION OF TRACTOR

AVAILABLE OPTIONS

-  REAR BLADE EXTENSIONS
-  HIGHWAY SAFETY REFLECTOR