

Cut and trim trees and brush, grub out small stumps and roots with the cutting edge with teeth, then use the back edge to gather the debris into a tidy pile. Add your Thumb to the process and you have the ability to load and move the remaining debris. Hardee Excavator Cutter Heads allow you to work efficiently with no down time due to attachment changes, or increasing costs by bringing in extra equipment. Two models available standard (STD) or heavy duty mulching (HDM).



GENERAL SPECIFICATIONS FOR HARDEE'S EXCAVATOR HEADS

SIZES	36"	42"	48"
MINIMUM EXCAVATOR WEIGHT	7500 LBS	10,000 LBS	14,000 LBS
SHIPPING WEIGHT	540 LBS	640 LBS	750 LBS
HYDRAULIC FLOW RATE	10 TO 30 GALS PER MINUTE (NO CASE DRAIN REQUIRED) RELIEF VALVE PROTECTED		
DECK CONSTRUCTION	1/4" THICK GRADE 50 (RE-ENFORCED)		
MOUNTING BRACKET	BOLT ON PER MACHINE REQUIREMENTS (PIN ON OR QUICK ATTACH)		
BLADE HOLDER	2 – GRADE A400 BLADES WITH GRADE 50 BLADE CARRIER		
CUTTING CAPACITY	UP TO 4"		
HYD. MOTOR/GEAR BOX	HIGH TORQUE MOTOR DIRECT MOUNTED AND COUPLED TO HD GEAR BOX		
WARRANTY	1 YEAR LIMITED WARRANTY		
ALSO INCLUDES	8ft HYDRAULIC HOSES with QUICK CONNECT COUPLERS		

****PLEASE CONTACT LOCAL DEALER FOR MORE INFORMATION****

4895 Red Bluff Road, Loris SC 29569
www.hardeebyevh.com

Phone: (843)756-2555 Fax: (843)756-4436
info@hardeebyevh.com